

HydraTech PolyLube

Long Term Storage for Polyurea Equipment

Issue 10.14

PRODUCT DESCRIPTION

PolyLube is a specially formulated low volatility plasticizer blend for use as 'A' side pump lubricant as well as the preferred media for long term storage of pumps and hoses. PolyLube helps retain the integrity of hoses and seals when equipment is not in use. Polyurea and foam spray equipment cleaned with PolyFlush and purged with PolyLube will ensure consistent operations with low maintenance over the life of the equipment.

Limitations

Not recommended for use as a cleaning or flushing material, the use of PolyFlush for such applications is highly recommended. Ensure PolyLube is completely purged from equipment prior to application.

Health & Safety

Consult product MSDS supplied separately.

Shelf Life & Storage

The product has a shelf life of six months when stored in the original unopened containers and not subject to temperatures below 70°F and above 130°F.

PHYSICAL PROPERTIES

| | |
|-------------------------------|----------------------|
| Appearance | Clear Liquid |
| Vapor Pressure | < 0.08 mm Hg @ 68 °F |
| Melting/Freezing Point | - 58 °F |
| Specific Gravity | 0.96 |
| Density | 8.06 lb./gal |
| Evaporation Rate | Negligible |
| Flash Points | CLOSED CUP: >437 °F |

INSTRUCTIONS FOR USE

After each use, flush equipment with PolyFlush to purge out all product and clean wetted parts. Once equipment is clean, PolyFlush is to be purged out and replaced with PolyLube for storage. Avoid the introduction of air into the equipment and maintain positive pressure in lines when system is closed.

Prior to equipment start up, PolyLube is to be purged out and replaced with product to be sprayed.

When utilizing PolyLube as lube for A side pumps, fill reservoir with PolyLube and replace with clean PolyLube on a regular basis.

